


IMPROVED PROCEDURES FOR DETERMINING SEISMIC SOURCE DEPTHS FROM DEPTH PHASE INFORMATION

QUARTERLY REPORT

Edward Page Richard Houck

January 1, 1978 to March 31, 1978



Sponsored by:
Advanced Research Project Agency
ARPA Order No. 1620

APPROVED FOR PUBLIC RELEASE DISTRIBUTION UNLIMITED

78 08 17 012

## Notice of Disclaimer

The views and conclusions contained in this document are those of the author and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Advanced Research Projects Agency, the Air Force Technical Applications Center, or the U.S. Government.

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)	
REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
Quarterly rept. 1 Jan-31	Nan 78
Improved Procedures for Determining Seismic Source Depths from Depth Phase	Quarterly Report 1/1/78-3/31/78
Information. #A052518	6. PERFORMING ORG. REPORT NUMBER  8. CONTRACT OR GRANT NUMBER(*)
Edward Page, Richard Houck 15	F\$8686-77-C-8887
ENSCO, Inc., 5408A Port Royal Road Springfield, VA 22151	VT/7710
11. CONTROLLING OFFICE NAME AND ADDRESS	May 78
VELA Seismological Center 312 Montgomery Street Alexandria, VA 22314	Unclassified  Unclassified  SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)	
APPROVED FOR PUBLIC RELEASE	
DISTRIBUTION UNLIMITED	
17. DISTRIBUTION STATEMENT (of the abetract entered in Block 20, if different fro	om Report)
18. SUPPLEMENTARY NOTES	
19. KEY WORDS (Continue on reverse elde if necessary and identify by block number,	
Seismic depth, depth phase, echo detection	n
All planned program development work on the Center (SDAC) version of the source depth has been completed. In addition, the program to process seismograms from the Area of In One event, AI Event No. 1 (7/26/77), was a depth estimate of 21 Km was obtained.	ne Seismic Data Analysis determination program gram has been modified nterest (AI) data set.
DD 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE	ASSIFICATION OF THIS PAGE (When Data Entered)

F-200.1473
ARMED SERVICES PROCUREMENT REGULATION

Hu

SUBJECT: Improved Procedures for Determining Seismic Source Depths from Depth Phase Information

AFTAC Project No	VELA T/8710
ARPA Order No	2251
ARPA Program Code No	6F10
Name of Contractor	ENSCO, INC.
Contract No	F08606-77-C-0007
Effective Date of Contract	1 October 1977
Reporting Period	1 January 1978 to 31 March 1978
Amount of Contract	\$160,833
Amount of Last Contract Modification	\$70,910
Contract Expiration Date	30 September 1978
Project Scientist	Edward A. Page (703)321-9000

ACCESS	ON for				
NTIS	٠,	Whit	e Se	ction	D
DDC		Buff			
UNANNO	DUNCED				
JUSTIFI					
BY			AU 171	. 000	
DISTRI	BUTION/A				
DISTRI	BUTION/A				

## INTRODUCTION AND SUMMARY

During this quarter, program development was completed, and processing of events from the Area of Interest (AI) data set was started. The final program development work consisted of implementation of the new significance level and narrow band threshold algorithms developed during the previous quarter. After this was completed, the program was modified to read seismograms from AI data tapes. The first event in this data set, AI Event No. 1, was processed and a depth estimate of 21 Km was obtained.

## MAJOR ACCOMPLISHMENTS

All planned program development tasks have been completed. The final work, completed during this quarter, was the implementation of the new significance level and narrow band threshold algorithms, which are described in detail in the previous Quarterly Report. Briefly, the new significance level algorithm gives improved significance level estimates, along with estimated significance level standard deviations. The narrow band threshold algorithm computes the shallowest interpretable depth, resulting from data bandwidth, for a given set of seismograms. Both of these program features are designed to aid the analyst in interpreting the final depth plots.

Processing of AI data was started by modifying the depth determination program to read seismograms from the AI data tapes. In its present form, the program is capable of reading seismograms from Seismic Research Observatory (SRO) and

Special Data Collection System (SDCS) stations, assuming seismogram numbers are in increasing order on an event tape. Array data can also be processed, but a maximum of 15 stations can be used, and seismograms with different sample intervals cannot be mixed in a single run. More data can be processed if additional program modifications are made.

The first event in the AI data set, AI Event No. 1 (7/26/77), was run to test these modifications. Seismograms from five SRO stations were processed; these are shown in Figure 1. Cepstrums were computed using 12.8 sec. windows for the first 51.6 sec. of each seismogram. In the time interval examined, only P arrivals were significant, and the resulting P depth plot is shown in Figure 2. From this plot, the estimated source depth for AI Event No. 1 is 21 Km; further analysis is necessary, however, before reliability grade can be assigned to this estimate.





Figure 1. AI Event No. 1, Seismograms

P PHPSE



DEPTH PLOTS

THE SET IS THE SET IS SET IN THE SET IN TH




Figure 2. AI Event No. 1, P Depth Plot